



ELECTRONIC TEST:
 1.OPEN/SHORT/INTERMITTE:100%.
 2.INSULATION RESISTANCE:5MΩ.
 3.CONTACT RESISTANCE:10Ω.
 4.HI-POT:300V 10ms

| | | | |
|-----|---------------------------|------|------|
| 3 | PVC SSP MOLD COLOR: BLACK | PCS | 1 |
| 2 | MICRO SATA16P CABLE SIDE | PCS | 1 |
| 1 | SATA 22PIN PCB SIDE | PCS | 1 |
| ND. | DESCRIPTION | UNCT | Q'TY |

| | | | | | |
|------|-------------|----------|------|------|----------------------|
| REV. | DESCRIPTION | DATE | SIZE | REV. | FILE NAME: |
| A | | 09/05/08 | A4 | A | CPU-SATA22P-MICCS16C |

UNLESS OTHERWISE SPECIFIED TOLERANCE:
 ANG. ±0.5
 .0 ±0.3
 .00 ±0.2
 SCALE: 1:1
 UNIT: MM

Cpu Stuff
 sales@cpustuff.com
 949-713-9070

DRAWN NAME: CPU-SATA22P-MICCS16C
 CHECKED: eric
 APPROVED: 09/05/08
 PRODUCT NO.: